

MA60





- **Trincia stocchi**
- Flail mowers
- **Decespogliatori**
- Rotary cutters
- **Applicazioni varie**
- Miscellaneous applications
- **Frese**
- Tillers



Montaggio • Assembly • Montage • Type d'assemblage • Montaje



Alberi • Shaft • Wellen typ • Type d'arbre • Tipos de eje

 <p>CH 36 mm 41 mm</p> <p>A-C</p>	 <p>S Ø 30 mm Ø 35 mm</p> <p>A-B-C-D</p>	 <p>V 1 3/8" Z6 DIN 9611</p> <p>A-B-C-D</p>	 <p>Vuoto Hollow 1 3/8" Z6</p> <p>A-C</p>
--	---	--	--

Dati Tecnici - Technical data - Technischen Daten - Données techniques - Datos técnicos

Peso • Weight • Gewicht • Poids • Peso

18 Kg

MA60

Olio • Oil • Öl • Huil • Aceite

1,0 Lt

Rapporto Ratio	Giri/Min Revolution/m	Potenza Power HP(Kw)	Kw	Coppia Entrata Torque Input	Coppia Uscita Torque Output	Input
1:1,92	540	50	37	650	339	A-B-C-D
	1000	70	51	490	255	
1:1,46	540	53	39	689	472	A-B-C-D
	1000	73	54	511	350	
1:1,35	540	60	44	780	578	A-B-C-D
	1000	75	55,1	525	389	
1:1,20	540	60	44	780	650	A

Optional

Ruota libera	Overrunning clutch	Freilauf	Rouelibre	Ruedalibre
Kit attacco pompa GR.2	Kit far pump connection	Getriebe mit pumpenanschluss	Kit d'attaque pompe	Kit conexión bomba incorporada
Cuscinetti di alta qualità	Quality bearings	Qualitätslager	Roulements de qualité	Rodamientos de calidad
Ingranaggi denti elicoidali	Helical teeth bevel/ gears	Zahnrad schrag verzahnt	Couple conique à denture hélicoïdale	Par cónico de dientes helicoidales
Prolunga	Extension	Verlängerung	Transmission	Transmisión
Anelli tenuta viton	Viton oil seal	Viton dichtungen	Joints viton	Retenes de viton
Albero cavo (Cilindrico/Esagonale)	Hollowshaft	Hohlwelle	Arbre creux	Eje hueco
Kit quarto asse	Kit 4th. Shaft	Getriebe mit vier Welle	Quatre arbre	Kit cuarto eje